

## KEY FEATURES

1–3 meter GPS with integrated SBAS

Microsoft Windows Mobile Version 5.0 software for Pocket PC, allowing maximum flexibility in software choice

512 MB onboard memory plus removable SD memory

Bluetooth and wireless LAN connectivity options

Rugged handheld with all-day battery



## THE ESSENTIAL GPS PLATFORM FOR MOBILE GIS

The Trimble® GeoXM™ handheld is the affordable, all-in-one mobile GIS solution you've been waiting for.

With a GeoXM handheld, your crews will collect reliable, 1-3 meter GPS data for your GIS, relocating assets with confidence and fulfilling work orders efficiently. And with its built-in Bluetooth® and wireless LAN connectivity, there will be fewer trips to the office, resulting in faster service and more satisfied customers.

### Software to fit your workflow

The GeoXM handheld comes with a powerful 416 MHz processor running the most advanced operating system available—Microsoft® Windows Mobile™ Version 5.0 software for Pocket PC.

Windows Mobile Version 5.0 features familiar Microsoft software, including Pocket Word, Pocket Excel, and Pocket Outlook®. And because it is the industry standard open platform for mobile devices, you can choose a software solution to match your workflow, whether off-the-shelf or purpose built.

### Convenient connectivity

With the GeoXM handheld you have the flexibility to work exactly the way you want to. Do you need to access the Internet or your organization's secure network to get the most up-to-date data? No problem—with the GeoXM handheld you have built-in wireless LAN and Bluetooth technology to ensure you stay connected.

When connection to your enterprise database isn't an option, the GeoXM handheld offers plenty of secure onboard memory for storing your data. And there's a Secure Digital (SD) memory card slot, allowing you to add gigabytes of memory for all your map data.

### Built for the field

The GeoXM handheld has an integrated battery, good for a full day's work; simply charge the battery overnight and you're ready to go again. The GeoXM handheld will

last the distance, and its rugged design can take a lot of punishment. Rain, hail, or shine, it's built to keep working, whatever the weather throws at you.

### Reliable GPS accuracy

Because the GPS receiver and antenna are built into the handheld computer, it's never been easier to use GPS in your application. The GeoXM handheld delivers reliable 1–3 meter GPS positions when and where you need them.

You can differentially correct in real time, using corrections from a satellite-based augmentation system (SBAS) such as WAAS or EGNOS or even use the integrated Bluetooth radio to connect to a Trimble GeoBeacon™ receiver. For extra precision, collect data using Trimble's TerraSync™ software or the GPScorrect™ extension for ESRI ArcPad software, then postprocess it back in the office.

### Improve the way you work

If you're serious about improving the way you work, choose the GeoXM handheld from Trimble. It's a rugged handheld that delivers reliable GPS positioning for your GIS—and with flexible options for wireless connectivity, and removable memory, you'll never be caught short in the field.

Wherever your work takes you, take your GIS with you on a GeoXM handheld.

## STANDARD FEATURES

### System

- Microsoft Windows Mobile Version 5.0 for Pocket PC
- 416 MHz Intel X-Scale processor
- 512 MB non-volatile Flash data storage
- Sealed SD card slot
- Outdoor color display
- Ergonomic cable-free handheld
- Rugged and water-resistant design
- All-day internally rechargeable battery
- Bluetooth wireless
- 802.11b wireless LAN

### GPS

- 1–3 m accuracy in real-time
- Integrated SBAS<sup>1</sup>
- RTCM real-time correction support
- NMEA and TSIP protocol support

### Software

- GPS Controller for control of integrated GPS and in-field mission planning
- GPS Connector for connecting integrated GPS to external ports
- Microsoft ActiveSync®, Calculator, File Explorer, Internet Explorer, Pictures, Pocket Excel, Pocket Outlook (Inbox, Calendar, Contacts, Notes, Tasks), Pocket Word, Windows® Media Player
- Transcriber (handwriting recognition)
- Microsoft Streets & Trips/AutoRoute software™

### Accessories

- Support module with power supply and USB data cable
- Getting Started Guide
- Getting Started Disc includes Outlook 2002 and ActiveSync 4.0
- Hand strap
- Pouch
- Stylus kit

## OPTIONAL FEATURES

### Software

- TerraSync software
- Trimble GPSCorrect extension for ESRI ArcPad software
- GPS Pathfinder® Tools Software Development Kit (SDK)
- GPS Pathfinder Office software
- Trimble GPS Analyst™ extension for ESRI ArcGIS software

### Accessories

- Serial clip for field data and power input
- Vehicle power adaptor<sup>2</sup>
- Portable power kit<sup>2</sup>
- Hurricane antenna kit
- External patch antenna
- Pole-mountable ground plane
- Baseball cap with patch antenna pocket
- GeoBeacon receiver
- Hard carry case
- Null modem cable<sup>2</sup>
- Backpack kit
- 2 meter range pole
- Range pole bracket

© 2002–2005, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GeoExplorer, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark Office and in other countries. GeoBeacon, GeoXM, GPS Analyst, GPSCorrect, and TerraSync are trademarks of Trimble Navigation Limited. ActiveSync, AutoRoute, Microsoft, Outlook, Windows, and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. TID13312H (10/05)

## TECHNICAL SPECIFICATIONS

### Physical

Size	21.5 cm × 9.9 cm × 7.7 cm (8.5 in × 3.9 in × 3.0 in)
Weight	0.78 kg (1.76 lb) with battery
Processor	416 MHz Intel PXA-270 X-Scale processor
Memory	64 MB RAM and 512 MB internal Flash disk
Power	
Low (no GPS or backlight)	1.5 Watts
Normal (with GPS and backlight)	2.3 Watts
High (with GPS, backlight, Bluetooth, and wireless LAN)	3.2 Watts
Battery	Internal 6800 mAh lithium-ion, rechargeable in unit 25 Watt-hours

### Environmental

Temperature	
Operating	–10 °C to +50 °C (14 °F to 122 °F)
Storage	–20 °C to +70 °C (–4 °F to 158 °F)
Casing	Wind-driven rain and dust-resistant per IP 54 standard Slip-resistant grip, shock and vibration resistant

### Input/output

Communications	Bluetooth <sup>3</sup> , 802.11b wireless LAN USB client v1.1 compliant <sup>4</sup> via support module Serial via optional DE9 serial clip adaptor Ethernet 10/100 BaseT compatible via support module
Bluetooth Profiles	
Client and host support	Serial Port, Object Push
Client support only	Dial-Up Networking
Host support only	File Transfer (using OBEX)
Display	Advanced outdoor TFT, 240 × 320 pixel 65,536 colors, with backlight
Audio	Microphone and speaker, record and playback utilities
Interface	Touch screen, Soft Input Panel (SIP) virtual keyboard 11 hardware control keys, handwriting recognition software Audio system events, warnings, and notifications

### GPS

Channels	12 (L1 code only)
Integrated real-time	SBAS <sup>1</sup>
Update rate	1 Hz
Time to first fix	30 seconds (typical)
Protocols	TSIP, NMEA (GGA, VTG, GLL, GSA, ZDA, GSV, RMC)

### Accuracy (HRMS)<sup>5</sup> after differential correction

Postprocessed	1–3 m
Real-time (SBAS <sup>1</sup> or external RTCM source)	1–3 m

<sup>1</sup> SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only. And EGNOS (European Geostationary Navigation Overlay System) available in Europe only.

<sup>2</sup> Serial clip also required.

<sup>3</sup> Bluetooth and wireless LAN type approvals are country specific. GeoExplorer 2005 series handhelds have Bluetooth and wireless LAN approval in the U.S. and EU. For other countries please consult your local Distributor.

<sup>4</sup> Fully compatible with USB v2.0 computers.

<sup>5</sup> Horizontal Root Mean Squared accuracy. Requires data to be collected with minimum of 4 satellites, maximum PDOP of 6, minimum SNR of 39 dBHz, minimum elevation of 15 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception. Accuracy varies with proximity to base station by +1 ppm for postprocessing and real-time.

Specifications subject to change without notice.



### NORTH & SOUTH AMERICA

Trimble Navigation Limited  
7401 Church Ranch Blvd  
Westminster, CO 80021  
USA  
+1-720-887-4374 Phone  
+1-720-887-8019 Fax

### EUROPE, AFRICA & MIDDLE EAST

Trimble GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY  
+49-6142-2100-0 Phone  
+49-6142-2100-550 Fax

### ASIA-PACIFIC

Trimble Navigation Australia  
PTY Limited  
Level 1/120 Wickham Street  
Fortitude Valley, QLD 4006  
AUSTRALIA  
+61-7-3216-0044 Phone  
+61-7-3216-0088 Fax